

Data Sheet

FUJITSU Desktop ESPRIMO D556/E85+

Your Flexible and Economic PC

The FUJITSU ESPRIMO D556/E85+ Desktop provides high-quality computing for your daily office tasks. It supports attractive price points and delivers the continuity needed for daily operations. Your valuable business data is protected by the latest TPM controller and the Erasedisk option. To meet your specific hardware needs it can be either individually configured or customized.

High performance and best price/performance ratio

Powerful and cost-effective small form factor desktop

- 6th generation Intel® Core™ processor family

System management

The perfect answer to offload your IT administrators

- DeskView Admin enhances the management of the devices in your IT infrastructure during productive operation – even during remote periods and after hours

Made in Germany

Outstanding quality and stable functions based on German production standards

- The development, production and functionality tests - all under one roof in Germany

Lifecycle

Hardware continuity for long-lasting project requirements

- Managed lifecycle up to 12 months

Meets ENERGY STAR® requirements

Low power consumption and low costs, without any loss in performance

- 85% energy efficient power supply



Components

Processor	<p>Intel® Core™ i7-6700 processor (4 Cores / 8 Threads, 3.40 GHz, up to 4.0 GHz, 8 MB, Intel® HD Graphics 530) *</p> <p>Intel® Core™ i5-6600 processor (4 Cores / 4 Threads, 3.30 GHz, up to 3.9 GHz, 6 MB, Intel® HD Graphics 530) *</p> <p>Intel® Core™ i5-6500 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 530) *</p> <p>Intel® Core™ i5-6400 processor (4 Cores / 4 Threads, 2.70 GHz, up to 3.3 GHz, 6 MB, Intel® HD Graphics 530) *</p> <p>Intel® Core™ i3-6100 processor (2 Cores / 4 Threads, 3.70 GHz, 3 MB, Intel® HD Graphics 530)</p> <p>Intel® Pentium® processor G4500 (2 Cores / 2 Threads, 3.50 GHz, 3 MB, Intel® HD Graphics 530)</p> <p>Intel® Pentium® processor G4400 (2 Cores / 2 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 510)</p> <p>Intel® Celeron® processor G3900 (2 Cores / 2 Threads, 2.80 GHz, 2 MB, Intel® HD Graphics 510)</p> <p>*with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)</p>
Operating systems	
Operating system	<p>Windows 10 Pro</p> <p>Windows 10 Home</p> <p>Windows 8.1 Pro</p> <p>Windows 8.1</p> <p>Windows 7 Professional 64-bit</p> <p>Windows 7 Professional 32-bit</p>
Operating system compatible	<p>Windows 10 Pro (license + recovery media only)</p> <p>openSUSE Linux</p>
Microsoft OS support information	<p>This system receives full support from Microsoft with Windows 10/Windows 10 Pro only. For any other Microsoft OS installed, this device has limited support from Microsoft. For more information, please see Microsoft's Support Lifecycle FAQ.</p>
Operating system notes	<p>This system receives full support from Microsoft with Windows 10/Windows 10 Pro only. For any other Microsoft OS installed, this device has limited support from Microsoft. For more information, please see Microsoft's Support Lifecycle FAQ.</p>
Memory modules	<p>4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM</p> <p>8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM</p> <p>16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM</p>
Hard disk drives (internal)	<p>SSD SATA III, 512 GB, 2.5-inch</p> <p>SSD SATA III, 256 GB, 2.5-inch</p> <p>SSD SATA III, 512 GB, 2.5-inch, SED</p> <p>SSD SATA III, 256 GB, 2.5-inch, SED</p> <p>SSD SATA III, 128 GB, 2.5-inch, SED</p> <p>SSD SATA III, 128 GB, 2.5-inch</p> <p>SSHD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch</p> <p>SSHD SATA III, 5,400 rpm, 500 GB, 2.5-inch</p> <p>HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical</p> <p>HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch, business critical</p> <p>HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch</p> <p>HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch</p> <p>HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch</p> <p>HDD SATA II, 5,400 rpm, 500 GB, 2.5-inch*</p>
Hard disk notes	<p>Up to 20 GB of HDD space is reserved for system recovery</p> <p>SSHD (Solid State Hard Disk, Hybrid drive)</p> <p>SSD (Solid State Disk)</p> <p>SED (Self-Encrypting Drive)</p>

Graphics	VGA Extension Card NVIDIA® NVS™315 LP, 1 GB NVIDIA® GeForce® GTX 745 2 GB LP, 2 GB NVIDIA® GeForce® 605 DisplayPort 1GB LP, 1 GB LFH59/ 2x DVI-I adapter cable LFH59/ 2x DP adapter cable DVI-I to VGA Adapter DP to DVI-D (single link) Adapter Cable
Drives (optional)	BD Triple Writer SATA ultra slim (tray) DVD Super Multi ultra slim (tray) MultiCard Reader 24in1 USB 2.0 3.5"
Interface add on cards/components (optional)	WLAN 802.11ac (2x2) PCIe x1 LP and BT 4.1 (dedicated regions only, up to BT 4.2 depending on OS version) WLAN 802.11ac (2x2) PCIe x1 LP (dedicated regions only) Gigabit Ethernet PCIe x1, DS eSATA Interface Dual serial card PCIe x1

Base unit

Base unit	ESPRIMO D556/E85+
Mainboard	
Mainboard type	D3430
Formfactor	proprietary
Chipset	Intel® H110
Processor socket	LGA 1151
Processor quantity maximum	1
Supported capacity RAM (max.)	32 GB
Memory slots	2 DIMM (DDR4)
Memory frequency	2,133 MHz
Memory notes	Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same.
LAN	10/100/1,000 MBit/s Realtek RTL8111G
BIOS version	AMI Aptio V
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) CSM (Compatibility Support Module)
Audio type	On board
Audio codec	Realtek ALC671
Audio features	Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound
I/O controller on board	
Serial ATA total	3
thereof SATA III	3
thereof eSATA	1
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI

Interfaces

Audio: line-in	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	6
USB 3.0 total	4
USB front	2x USB 2.0; 2x USB 3.0
USB rear	2x USB 2.0; 2x USB 3.0
USB internal	2x USB 2.0
VGA	optional: via adapter card
DisplayPort	1
DVI	1 (DVI-D)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality

Input device / components

Input devices (optional)	Keyboard Mouse KBPC PX ECO Mouse M440 ECO
--------------------------	--

Drive bays

3.5-inch internal bays	1
3.5-inch external bays	1
5.25-inch external bays	1
Drive bay notes	5,25" bay: for slim optical disc drive only; internal 3.5" bay: 1x 3.5" drive (screwless) or 1x 2.5" drive (screws) or optional via adapter for 1x or 2x 2.5" drives (screws); external 3.5" bay: optional as internal 3.5" bay (screws)

Slots

PCI-Express 3.0 x16	1 x (174 mm / 6.85 inch) Low profile
PCI-Express 2.0 x4 (mech. x16)	1 x (174 mm / 6.85 inch) Low profile
PCI-Express x1	1 x (174 mm / 6.85 inch) Low profile

Graphics on board

Graphics brand name	Intel® HD Graphics 510, Intel® HD Graphics 530
Shared video memory	up to 1,782 MB
TFT resolution (VGA)	1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel
TFT resolution (DVI)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel

Graphics on board

TFT resolution (DisplayPort)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,600 pixel 3,840 x 2,160 pixel 4,096 x 2,304 pixel
Graphics features	Dual display support DirectX® 12 HDCP support OpenCL™ 2.0 (requires Intel® Core™ i3, i5 or i7 processors) OpenGL® 4.4 For multi monitoring mode, graphics card and integrated graphics run in parallel DisplayPort interface supports Ver. 1.2 incl. Multi-Stream DVI-D interface supports audio output for HDMI monitors
Graphics notes	up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

Electrical values

Power efficiency note	power supply efficiency (at 230V; 10% / 20% / 50% / 100% load) : 75% / 83% / 85% / 84%
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	280 W
Power factor correction/active power	active
Monitor outlet	No

Power consumption

Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=08b148de-e92a-409f-825a-e6fd66487c0a

Heat dissipation

Heat dissipation notes	See white paper Energy Consumption
-------------------------------	------------------------------------

Noise emission

Related Processors for noise	Intel® Core™ i7 6700
Standard noise emission	2x4 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level Lw _{ad} (in B) / Workplace related A-weighted sound pressure level Lp _{Am} (in dB(A))
Standard noise operation mode: CPU 50% load	3.5 B / 22 dB(A) Bystander; 25 dB(A) Operator position
Standard noise operation mode: HDD load	3.3 B / 20 dB(A) Bystander; 21 dB(A) Operator position
Standard noise operation mode: Idle mode	3.3 B / 19 dB(A) Bystander; 21 dB(A) Operator position
Standard noise operation mode: ODD load	4.4 B / 30 dB(A) Bystander; 34 dB(A) Operator position
Standard noise operation mode: Office applications 2.0	3.3 B / 19 dB(A) Bystander; 21 dB(A) Operator position
Blue angel noise emission according certification	According to ISO 7779:2010, ECMA-74 for max. possible configuration
Blue angel noise notes / description	A-weighted sound power level Lw _{ad} (in B); 1B = 10dB

Noise emission

Blue angel noise operation mode: HDD load 3.5 B = 35 dB (A)

Blue angel noise operation mode: Idle mode 3.5 B = 35 dB (A)

Blue angel noise operation mode: ODD load 4.7 B = 47 dB (A)

Dimensions / Weight / Environmental

Dimensions (W x D x H) 332 x 338 x 89 mm
12.68 x 13.31 x 3.51 inch

Operating position horizontal / vertical (optional, feet needed)

Weight 8 kg

Weight (lbs) 17.64 lbs

Weight notes Actual weight may vary depending on configuration

Operating ambient temperature 10 - 35 °C (50 - 95 °F)

Operating relative humidity 5 - 85 % (relative humidity)

Compliance

Product ESPRIMO D556/E85+

Model DTF

Germany TÜV GS

USA/Canada FCC Class B
cCSAus

Global RoHS (Restriction of hazardous substances)
WEEE (Waste electrical and electronic equipment)
Microsoft Operating Systems (HCT / HCL entry / WHQL)
ENERGY STAR® 6.1 (dedicated regions)
EPEAT® Gold (dedicated regions)

China CCC

Compliance link <http://globalsp.ts.fujitsu.com/sites/certificates>

Additional Software

Additional software (preinstalled) Adobe® Reader® (pdf reader)
McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version)
Win7: Fujitsu Recovery (hard disk based recovery)
Win8: Microsoft Push Button Recovery (hard disk based recovery)
Microsoft Office (buy license to activate the pre-installed Microsoft Office)

Additional software (optional) Recovery DVD for Windows®
Drivers & Utilities DVD (DUDVD)
CyberLink PowerDVD BD (playback software for Blu-ray Disc™)
CyberLink PowerDVD DVD (playback software for DVD)
Nero Essentials XL

Manageability

Manageability technology DeskUpdate Driver management
PXE 2.1 Boot code
Wake up from S5 (off mode)
Intrusion switch (optional)
WoL (Wake on LAN)

Manageability software DeskView Client
DeskView Instant BIOS Management

DeskView components Inventory Management
BIOS Management
Driver Management
Security Management
Alarm Management

Manageability

Supported standards	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)
----------------------------	--

Security

Physical Security	Kensington Lock support Eye for padlock Integrated cabinet lock (optional)
System and BIOS Security	Embedded security (TPM 2.0) EraseDisk (optional) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces
User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) Workplace Protect (secure authentication solution)
Workplace Embedded Tools	Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server (optional) Easy PC Protection (optional)

Miscellaneous

Keyboard on (Special Fujitsu keyboard required)
Thermal management

Serviceability

EasyFix
EasyChange for HDD
EasyChange for optical drives

Packaging information

Packaging dimension (mm)	467 x 265 x 540 mm
Packaging dimension (inch)	18.39 x 10.43 x 21.26 inch
Max. quantity / pallet	28
Material - Weight (g) Carton	1180 g
Material - Weight (lbs) Carton	2.6 lbs
Material - Weight (g) EPS / PS	180 g
Material - Weight (lbs) EPS / PS	0.4 lbs
Material - Weight (g) PE	60 g
Material - Weight (lbs) PE	0.13 lbs
Packaging notes	printed user documentation is bleached in chlorine free process

Warranty

Warranty period	1 year (for countries in EMEA)
Warranty type	Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty

Product Support Services - the perfect extension

Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

Recommended Accessories

Display B24-8 TE Pro



The FUJITSU Display B24-8 TE Pro is made for intensive office work. With visual and mechanical ergonomics this marble-grey display enables fatigue-free working for hours in front of the screen. The large 60.5 cm (23.8-inch) screen allows you to keep always track of all open applications. This high-quality display works unfailingly around the clock. Easy connectivity, manageability and usability help you increase your productivity.

Order Code:
S26361-K1577-V140

Mouse M440 ECO



Fujitsu Mouse M440 ECO is made from 100% bio material and has a completely PVC free cable. The elegant M440 ECO works on nearly every surface and follows all your hand movements smoothly and precisely. It features two main buttons and as well as a scroll wheel providing comfortable computing to both right and left-handed users.

Order Code:
S26381-K450-L200

UC&C USB Headset Stereo H650e



The UC&C USB Headset Stereo H650e is the ultimate in style and functionality. Long, uncomfortable work calls are a thing of the past thanks to the cushioned ear pads and crystal clear sound. Adjustable headband and microphone provides the perfect fit for everyone. Optimized for Microsoft® Lync™ the headset displays a red 'in-call' LED to let your co-workers know when you're available, thus helping to boost office productivity.

Order Code:
S26391-F7139-L10

Keyboard KBPC PX ECO



Fujitsu's KBPC PX ECO keyboard is the perfect contribution to Green IT. The keyboard is made out of 45% renewable raw material and comes with a PVC free USB cable. In addition, the KBPC PX ECO offers first class comfort and ergonomics. It attracts attention with its impressive modern design and useful extras.

S26381-K341-L1** (**:
country specific variation)

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Desktop ESPRIMO D556/E85+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Desktop ESPRIMO D556/E85+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2016 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions GmbH
Website: www.fujitsu.com/fts
2016-09-01 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2016 Fujitsu Technology Solutions GmbH