

Data Sheet

FUJITSU Display E19-7 LED

Advanced display 48.3 cm (19-inch)
Best energy saving solutions for office applications

The FUJITSU Display E19-7 LED combines comfortable ergonomics with best-in-class energy saving technology like ECO operation mode.

Environmentally friendly LED technology with unique, high efficient energy saving solutions like ECO operation mode and ECO standby

Convenient and fatigue-proof-usage due to visual ergonomics for the office ensured by In-Plane Switching (IPS) technology

Flexible connectivity with DVI and Analog

Representative design providing a slender housing in ergonomic matt black, integrated speakers and power supply

Support for FUJITSU Desktop ESPRIMO Q and FUJITSU Thin Client FUTRO backpack solutions



Technical details

Special features

In-Plane Switching (IPS) technology, LED backlight panel, Eco button for Eco mode and 3-coloured Eco status LED

Ergonomic stand

Stand removable
Tilt angle -5° / +20°

Picture performance

Panel and backlit IPS/LED
Screen Surface Treatment Anti-glare, 3H hard coating
Contrast - typical 1000:1
Contrast - advanced 2,000,000:1
Response time gray to gray typical 8 ms
Viewing angle (h/v) - typical 178°/178° CR10:1
Color performance 16.7 million colors (Hi-FRC)
Brightness - typical 250 cd/m²

Size and resolution

Aspect ratio 5:4
Diagonal Size 48.3 cm (19-inch)
Resolution (native) 1,280 x 1,024 pixel
Resolution (interpolated) 1,280 x 720 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 720 x 400 pixel, 640 x 480 pixel
Picture size 375 x 300 mm
Pixel Pitch 0.293 mm

Frequencies

Horizontal 30 - 82 kHz
Vertical 56 - 76 Hz
Frequencies - bandwidth 165 Mhz

Connectivity

DVI 1 x DVI-D (HDCP)
VGA/D-SUB 1 x D-SUB
Audio signal output 3.5 mm stereo phone jack for head phone
Audio signal input 3.5 mm stereo phone jack
Audio sound output 2 x 1.5 W

Ease-of-use menu

Languages Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional
Brightness / Contrast Brightness, Contrast, Black level, Auto level
Color sRGB, 6500K, 7500K, 9300K, Native, Custom Color (R,G,B)
Image adjust Clock, Phase, H-Position, V-Position
Audio Mute, Volume
Information Model name, Serial number, Resolution/mode, Signal input
Setup Input select, Language, DDC/CI, OSD-Timeout, Factory preset

Power consumption (typical)

Soft switch off 0.26 W
Power save mode 0.26 W
Operating with EPA settings 14.6 W
Operating maximum brightness 17 W
Power supply integrated
Power notes Speakers off

Electrical values

Rated voltage range 100 V - 240 V
Rated frequency range 50 Hz - 60 Hz

Protection class	1
Compliance	
Europe	Energy Efficiency Class: A, CE certification according to EC Directive 2004/108/EEC, EN 60950, RoHS, WEEE, IT-Eco-Declaration
Model	DY19-7
Germany	TÜV GS
Russia	EAC
USA/Canada	FCC Class B, cUL
Japan	VCCI
South Korea	KC (planned)
Singapore	S-Mark
Taiwan	BSMI (planned)
Saudi Arabia	SASO
Global	TCO Certified Displays 6.0, ENERGY STAR® 6.0, EPEAT® in progress (dedicated regions), ISO9241-307 (Pixel fault class I)
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates
Quality and Reliability	
MTBF (demonstrated)	70,000 h
Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	414 x 64 x 349 mm 16.3 x 2.52 x 13.74 inch
Dimension with stand (W x D x H)	414 x 209 x 391 mm 16.3 x 8.23 x 15.4 inch
Weight (packed)	4.9 kg 10.8 lbs
Weight (unpacked)	3.52 kg 7.76 lbs
Weight (Monitor only)	3.09 kg 6.8 lbs
Operating ambient temperature	5 - 35 °C
Miscellaneous	
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
Color	Black
Package content	
Display delivered accessories	D-SUB Data cable 1.8 m Audio cable 1.8 m Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m Quickstart flyer Utility CD Warranty booklet Safety booklet
Display delivered accessories notes	Data cables and audio cable detachable on display
Order information	
Order Code	S26361-K1482-V160
EAN Code	4053026421102
Country specific order code	BDL:K1482V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1482V160-CHN - with China power cable and CEL, mandatory for China BDL:K1482V160-ID - with Import label, mandatory for Indonesia BDL:K1482V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed
Accessories information	Further helpful options: Available Privacy Filters: http://globalsp.ts.fujitsu.com/dmsp/Publications/public/ds-Privacy-Filter.pdf Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf
Warranty	
Warranty period	3 years (depending on country)
Warranty type	Collect & Return Service (depending on country specific requirements)

Warranty

Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Display E19-7 LED, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Display E19-7 LED, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://www.fujitsu.com/fts/displays>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2016 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.